

## SI LIMITED LIABILITY COMPANY TANDEM LTD

## **PRODUCTS**

PRODUCT	TYPICAL APPLICATION	PRODUCT INFORMATION	OPTIONAL
PP WOVEN LAMINATED BLOCK BOTTOM BAGS (AD*STAR)	PACKING, STORAGE AND TRANSPORTATION OF LOOSE FREIGHT: ADRICULTURAL PRODUCTS; CHEMICALS; PETRO-CHEMICALS; FERTILIZERS; BUILDING MATERIALS AND COMPOUNDS.	WEIGHT: 83-96 g/m <sup>2</sup> WIDTH: 400-600 mm   LENGTH: 470-900 mm   TOP: VALVE / OPEN   BOTTOM WIDTH: 80-160 mm   VALVE LENGTH: 80-200 mm   LOADING CAPACITY: 9-75 kg   LAMINATION: PP+PE   FABRIC COLOR: AT CUSTOMER'S REQUEST	MICRO-PERFORATION PRINTING: 6-COLORS FLEXO UV STABILIZATION TRANSPARENT STRAP
PP WOVEN FLAT BAGS	PACKING, STORAGE AND TRANSPORTATION OF LOOSE FREIGHT: ADRICULTURAL PRODUCTS; CHEMICALS; PETRO-CHEMICALS; FERTILIZERS; BUILDING MATERIALS AND COMPOUNDS. CONSTRUCTION WASTE DISPOSAL.	WEIGHT: 58-100 g/m <sup>2</sup> WIDTH: 350-850 mm   GUSSETS WIDTH: 30-90 mm   LENGTH: 450-1290 mm   TOP: SEWN / THERMAL-CUT   TOP/BOTTOM SEAM: SINGLE / DOUBLE LOADING CAPACITY:   FABRIC COLOR: AT CUSTOMER'S REQUEST	INNERLINER: PE GUSSETS TRANSPARENT STRAP HANDLE LAMINATION: PP+PE PERFORATION PRINTING: 6-COLORS FLEXO UV STABILIZATION
PP WOVEN LENO / MESH BAGS	PACKING, STORAGE AND TRANSPORTATION OF: FRUIT; VEGETABLES; NUTS; FIREWOOD AND OTHER PIECE- GOODS.	WEIGHT:45 g/m²WIDTH:350-850 mmLENGTH:450-1250 mmTOP:THERMAL-CUT / TWINEBOTTOM SEAM:SINGLE / DOUBLELOADING CAPACITY:5-25 kgFABRIC COLOR:AT CUSTOMER'S REQUEST	UV STABILIZATION
PP WOVEN FABRIC	MAKING: BAGS, FIBC'S; LINERS, INSERTS AND CAPES FOR OPEN WAGONS AND GONDOLAS; PACKAGING: MACHINERY, CLOTHES. COVERING AND PROTECTION: LUMBER; AT TRANSPORTATION; INDUSTRIAL STORAGE: RUBBER, TIRES.	WEIGHT: 50-200 g/m <sup>2</sup> TUBULAR WIDTH: 200-2000 mm   FLAT WIDTH: 200-3400 mm   COLOR: AT CUSTOMER'S REQUEST	LAMINATION: PP+PE PERFORATION PRINTING: 6-COLORS FLEXO UV STABILIZATION TRANSPARENT STRAP
PP WOVEN ROOFING FILM	STRENGTHENING AND PREVENTION OF BASE FLASHES; CONDENSATION RISK REDUCTION; PROTECTION OF THE FRAME AND ANY SHEATHING FROM WATER / VAPOR; USED AT ROAD CONSTRUCTION.	WEIGHT: 65-120 g/m²   WIDTH: 1500 mm   LENGTH: 50 m   AREA: 75 m²   BARRIER: WARER / VAPOR   TENSILE STRENGTH: ≥300 N/50 mm   UV STABILIZATION ONE - / TWO-SIDE PP+PE   COLOR: SILVER   VAPOR PERMEABILITY: WATERPROOF:   WATERPROOF: ≥40 g/m²/24 hrs   VAPOPROOF: ≤1.5 g/m²/24 hrs	
PP WOVEN AGROTEXTILE	FUNCTIONS: FILTRATION, REINFORCEMENT AND SEPARATION USED IN: GARDENS, FLORICULTURE, SMALL GREENHOUSES, LANDSCAPING, TREE PLANTING, EROSION CONTROL, PAVING, SHADING, PROTECTION	WEIGHT: 100 g/m <sup>2</sup> WIDTH: 600-3000 mm   LENGTH: AT CUSTOMER'S REQUEST   UV STABILIZATION GREEN + BLACK STRIPES	

FOR FURTHER TECHNICAL INFORMATION OR IF YOU WISH TO DISCUSS YOUR REQUIREMENTS, PLEASE, CONTACT OUR **MARKETING & SALES DEPARTMENT:**